



**IA2541, 1** : Sonstige**Product number:**

IA2541


## Description

 120V / 1

8 - 12



GHI - Guinea Hermanos ingenieros



2008



7500



3500



80 A, 400 V, 3-Phasen, 50 Hz

□□□□

□□□

□□□□□□□□□

□□

□ 120□ /□□

□□□

8-12□□□□

□□

□□□

GHI - Guinea Hermanos ingenieros

□□

□□ TFA 5□□□

□□□□

2008

□□□□

25 t

□□□

5□ /□□

□□□□

□□

□□□

□□

□□

□□□□□

□□□□□

2.800.000□

□□

4

□□□□

□□□□□□□□□

□□□□□

30□□

□□□□□□

1100 °C

□□□ x□ x□

5000 x 6200 x 7200

□□□

30 KW, (60 A), □□□□□ 22 kW (44 A) □□□□  
TFA-5□ RAN-R-25-B□□□□ 400 V, 3Ph, 50 Hz□

□□□□□□

LOTUS

□□□□□□□□□□

□□□

TECHNI-THERM

□□□□□□ LOTUS  
□□□□□□□□□□

□□□□□□□□□□

□□□□□□ 2010

□□□□□□ 24 t

□□

□□□□□□ 6700□□

□□□□□□ 4700□□

□□

□□□□□□ 3600□□

□□□□□□ 3500□□

□□□□□□ 4400□□

□□□□□□ 800/900□□

□□□□□□ 3000 x 632 mm

□□□□□□ 2500□□

□□□□□□□□□□ 290 Nm<sup>3</sup>/h, □□

□□□□□□□□□□

□□□□□□□□□□ 4700 x 1200 mm

□□□□□□□□□□ 900 800□□

□□□□□□□□□□ LOTUS□ TT 35 SO□□ 11□□

□□□□□□ /□□□□

□□□□□□□□□□ GHI - □□□□□

□□□□□□□□□□

□□□□□□□□□□ 2008

□□□□□□□□□□ 25 t

□□

□□

□□□ /□□□

□□□□

950□□

□□□□

3400□□

□□□□□

□□

8600□□

□□

6500□□

□□

7800□□

□□□□

2.500.000 kcal/h

□□□□

2500□□

□□

□□

North-American Mfg. Co Allumage

□□□□□

□□

2

□□□□□□

18,5 kW, 3000 U/min

□□□□

□□□□

□□□□ (□ x□ )

4700 x 1200 mm

□□□□□

□□□

□□□□

□□

□□

□□□□

2008

□□□□

8 - 12□□

□□□□ /□□

ca.5 t/h

□□□□

□□

□□□□□□

□ /□□

□□□□□

□□

□□□□□

□□□□	
□□□□	19425□
□□	10080□
□□□□□	42070 mm
□□	□□□□□□
□□□□	
□□	□□□□
□□	2008
□□ □□ 1+2	60.000 Nm <sup>3</sup> /h
□□□□□	15.000 m <sup>3</sup> /h
□□□□	10 a' 15.000 m <sup>3</sup> /h
□□□□	5 a' 8.000 m <sup>3</sup> /h
□□ □	20 a' 25.000 m <sup>3</sup> /h
□□□	115 a' 120.000 m <sup>3</sup> /h
□□□	
□□□	
□□	40 mg/Nm <sup>3</sup>
Gurantee SEMECA	20 mg/Nm <sup>3</sup>
□□	
□	0,1 ng/Nm <sup>3</sup>
Gurantee SEMECA	0.1 ng/Nm <sup>3</sup>
□□	
□	50 mg/Nm <sup>3</sup>
Gurantee SEMECA	50 mg/Nm <sup>3</sup>
□□□	
□□	□□□
□□	□□□

